

01224 248821

info@lhrmarine.com

www.lhrmarine.com



Vertex Best Helmet for Work at Height

LHR UK 380 LVB

Certification

CE

ANSI Z89.1 - 2003

Type I class E

Technical specifications

Head band adjustable from 53 to 63 cm.

Available in yellow (A16 Y1) or black (A16 N1).

465 g.



Durable and comfortable helmet, meets requirements for work at height. Best suited for environment (height, rescue) Chinstrap designed to reduce the risk of the helmet coming off as a result of an impact during a fall

it has a breaking strength greater than 50 daN (EN 12 492 mountaineering helmet standard). Polycarbonate shell, resistant to impact and wear (meets EN 397 Industrial helmet standard and EN 12492 standard).

Meets all optional requirements of the EN 397 standard: lateral deformation, use at low temperatures (down to - 30 °C), electrical insulation, molten metal splash.

Customizable: side slots for mounting hearing and/or eye protection, the cut of the shell contours over the ears to fit standard hearing protection, four headlamp clips.

Complete and simple adjustment: single headband size adjustment wheel, quick and precise to manipulate even while wearing gloves, height adjustment of the headband to adjust the position of the straps on the neck, chinstrap buckles can be adjusted forwards and backwards.

Comfortable: webbing suspension system, thick, replaceable foam headband. The headband retracts into the shell for storage.

Please visit our website at www.lhrmarine.com or e-mail us at info@lhrmarine.com

“Quality and Service is the Foundation of Future Business”