

0474/12  
IMO Res. MSC 81(70)  
ISO 24408:2005

AQUA  
SPEC

AQ40S

datasheet  
NEW PRODUCT

## High Performance LED Lifejacket Light



5 times longer\*

More than 40 hours of continuous operation

\* Compared to 8 hour SOLAS minimum standard

3 times brighter\*

More than 2.5cd of illumination after 8 hours continuous use

\* Compared to 0.75cd SOLAS minimum standard


### Details

The AQ40S is a unique flashing lifejacket light, automatically water activated by the sensor points or manually at the touch of a button. Its unique size and shape, combined with ease of attachment, has made the AQ40S ideal for fitment to an inflatable lifejacket, suitable for both leisure and commercial applications.

### Features and benefits

- > Powerful white flashing LED dome light
- > With built in sensor points
- > Manual and automatic water activation
- > Functional and simple design
- > Fixing clip designed for easy attachment
- > Compact design
- > Maintenance free **five year battery life**
- > Tamper-proof

### Technical Specification

Colour	White LED
Activation	Water Auto / Manual
Dimensions	50mm (h) x 22mm (w) x 31mm (d)
Weight	29 grams
Battery Type	Lithium
Output	Minimum 2.5cd Light
Duration	Minimum 40hrs Light
Storage Life	5 Years from Date of Manufacture
Approvals	SOLAS (LSA Code), IMO Res MSC 81(70), ISO24408  MED Shipswheel approved 0474/12 USCG Approvals pending