

FIREBIRD FIRE HOSE EQUIPMENT CABINETS

INDUSTRIAL BOXES & CASES

1 OVERVIEW

Jo Bird & Co Ltd has long been recognised as a leading manufacturer of GRP storage cabinets for fire fighting and lifesaving equipment for use in some of the most inhospitable climates in the world. The ability to manufacture consistently to the highest standards demanded by multi-national oil exploration giants comes from a combination of innovative design, carefully controlled manufacturing conditions and above all, attention to detail.

The Firebird range of cabinets sets the standard by which others are measured and has consistently outperformed other products on the market. Individually accredited as a supplier to leading oil companies, Jo Bird & Co Ltd is also independently recognised for its quality standards under BS EN ISO 9001.



2 FEATURES

- ❑ Used to Store Fire Hose of Various Sizes
- ❑ Lloyds Register Type Test Approved
- ❑ IP56 IP Rating
- ❑ Manufactured From 3-4mm Nominal Thickness
- ❑ GRP
- ❑ Stainless Steel & Nylon Jaw Action Door Catch
- ❑ Quality Manufacture under BS EN ISO 9001 Standards

3 PRODUCT SPECIFICATIONS



TYPICAL USE: Storage for 1 X Length Fire 18m Fire Hose and Branch Pipe

APPROVAL: Lloyds Register Type Test Approved

IP RATING: IP56

HEIGHT X WIDTH X DEPTH (MM): 627 x 530 x 238

APERTURE (MM): 470H x 340W

INTERNAL DEPTH (MM): 185

WEIGHT (KG): 12

COLOUR: Red BS4800 04 E 53

MATERIAL: 3-4mm Nominal Thickness GRP

DOOR CATCH: Stainless Steel & Nylon Jaw Action

DOOR HANDLE: Recessed Nylon Rod

HINGES: Stainless Steel 'T' Hinge

SEAL: EPDM Seal

REINFORCEMENT: 150mm² Pads to Top and Bottom of Back

OPTIONAL EXTRAS: Lettering, Fire Retardancy and/or Window



TYPICAL USE: Storage of 2 X 30m Fire Hose and Branch Pipe

APPROVAL: Lloyds Register Type Test Approved

IP RATING: IP56

HEIGHT X WIDTH X DEPTH (MM): 930 x 812 x 320

APERTURE (MM): 756H x 630W

WEIGHT (KG): 19

COLOUR: Red BS4800 04 E 53

MATERIAL: 3-4mm Nominal Thickness GRP

DOOR CATCH: Stainless Steel & Nylon Jaw Action

DOOR HANDLE: Recessed Nylon Rod

HINGES: Stainless Steel 'T' Hinges

SEAL: EPDM Seal

REINFORCEMENT: 150mm² Pads of 12mm Ply to Top

OPTIONAL EXTRAS: Lettering, Fire Retardancy and/or Window



TYPICAL USE: Storage of Fire Hose

APPROVAL: Lloyds Register Type Test Approved

IP RATING: IP56

HEIGHT X WIDTH X DEPTH (MM): 765 x 685 x 334

APERTURE (MM): 600H x 500W

WEIGHT (KG): 15

COLOUR: Red BS4800 04 E 53

MATERIAL: 3-4mm Nominal Thickness GRP

DOOR CATCH: Stainless Steel & Nylon Jaw Action

DOOR HANDLE: Recessed Nylon Rod

HINGES: Stainless Steel 'T' Hinge

SEAL: EPDM Seal

REINFORCEMENT: 150mm² Pads to Top and Bottom of Back

OPTIONAL EXTRAS: Lettering, Fire Retardancy and/or Window



TYPICAL USE: Storage of 4 Lengths Fire Hose, Branch Pipe and Stand Pipe

APPROVAL: Lloyds Register Type Test Approved

IP RATING: IP56

HEIGHT X WIDTH X DEPTH (MM): 1295 x 625 x 450

APERTURE (MM): 1060H x 445W

INTERNAL DEPTH (MM): 365

WEIGHT (KG): 21

COLOUR: Red BS4800 04 E 53

MATERIAL: 3-4mm Nominal Thickness GRP

DOOR CATCH: Stainless Steel & Nylon Jaw Action

DOOR HANDLE: Recessed Nylon Rod

HINGES: Nylon PA 66

HOSE PIN: Stainless Steel Rod

SEAL: EPDM Seal

REINFORCEMENT: 12mm Pads Ply to Back Face

OPTIONAL EXTRAS: Lettering, Fire Retardancy and/or Window