

FIREBIRD FIRE HOSE & FOAM CABINETS

INDUSTRIAL BOXES & CASES

1 OVERVIEW

Jo Bird & Co Ltd has long been recognised as a leading manufacturer of GRP storage cabinets for fire fighting and lifesaving equipment for use in some of the most inhospitable climates in the world. The ability to manufacture consistently to the highest standards demanded by multi-national oil exploration giants comes from a combination of innovative design, carefully controlled manufacturing conditions and above all, attention to detail.

The Firebird range of cabinets sets the standard by which others are measured and has consistently outperformed other products on the market. Individually accredited as a supplier to leading oil companies, Jo Bird & Co Ltd is also independently recognised for its quality standards under BS EN ISO 9001.



2 FEATURES

- ❑ Used to Store Firefighter's Equipment of Various Sizes
- ❑ Lloyds Register Type Test Approved
- ❑ Red BS4800 04E53 Colour
- ❑ Manufactured From 3-4mm Nominal Thickness GRP
- ❑ Stainless Steel & Nylon Jaw Action Door Catch
- ❑ Quality Manufacture under BS EN ISO 9001 Standards

3 PRODUCT SPECIFICATIONS



TYPICAL USE: Storage for 2 x Breathing Apparatus and Firefighter's Clothing

APPROVAL: Lloyds Register Type Test Approved

IP RATING: IP56

HEIGHT X WIDTH X DEPTH (MM): 1528 x 910 x 495

APERTURE (MM): 1240H x 710W

INTERNAL DEPTH (MM): 410

WEIGHT (KG): 26

COLOUR: Red BS4800 04 E 53

MATERIAL: 3-4mm Nominal Thickness GRP

DOOR CATCH: Stainless Steel & Nylon Jaw Action

DOOR HANDLE: Recessed Nylon Rod

HINGES: Stainless Steel 'T' Hinge

SEAL: EPDM Seal

REINFORCEMENT: 150mm² Pads to Top Corners of Back

BA RETAINING CLIPS: Plastic Coated Sprung Steel x 2

OPTIONAL EXTRAS: Lettering, Fire Retardancy and/or 6mm Thick GRP



TYPICAL USE: Storage of 4 x Lengths Fire Hose, Branch Pipe and Stand Pipe

APPROVAL: Lloyds Register Type Test Approved

IP RATING: IP56

HEIGHT X WIDTH X DEPTH (MM): 1087 x 924 x 350

APERTURE (MM): 685H x 730W

WEIGHT (KG): 40

COLOUR: Red BS4800 04 E 53

MATERIAL: 3-4mm Nominal Thickness GRP

ROLLER SHUTTER: AS Fire Extreme Environment Roller Shutter

REINFORCEMENT: 150mm² Pads of 12mm Ply to Top Corners of Back

OPTIONAL EXTRAS: Lettering and/or Fire Retardancy



TYPICAL USE: Storage of Fire Hose & Equipment

APPROVAL: Lloyds Register Type Test Approved

IP RATING: IP56

HEIGHT X WIDTH X DEPTH (MM): 1773 x 910 x 460D

APERTURE (MM): 1335H x 764W

WEIGHT (KG): 60

COLOUR: Red BS4800 04 E 53

MATERIAL: 3-4mm Nominal Thickness GRP

ROLLER SHUTTER: AS Fire Extreme Environment
Roller Shutter

REINFORCEMENT: 2x 150mm² 6mm PVC Pads to
Back of Cabinet

OPTIONAL EXTRAS: Lettering, Fire Retardancy
and/or 6mm Thick Cabinet