



REBEL™ 3.3 AND 6 METER WEB AND 4.5 METER CABLE SELF-RETRACTING LIFELINE



PRODUCT OVERVIEW

LONGER, LIGHTER, SMALLER...

The Protecta® web line renewal extends the Rebel™ product excellence all across the range.

	Rebel™ 3.3 m Web	Rebel™ 6 m Web	Rebel™ 4.5 m Cable
Height (*)	48 cm	57 cm	74 cm
Width	15 cm	25 cm	15 cm
Depth	8 cm	12 cm	8 cm
Weight	1.4 kg	2.2 kg	2.8 kg

(*) Anchor point to anchor point

MATERIAL

Web : Polyester, 25 mm wide
 Cable : Galvanized, 5 mm diameter
 Recall spring material : Stainless steel
 Connection level : Can be connected from shoulder level
 Certification : CE EN360:2002
 Capacity : 140 kg
 Servicing : 6 m and 4.5 m units are repairable



TOP CONNECTOR

- Twist-lock zinc plated carabiner 16 kN gate strength, 18 mm opening

TOP SWIVEL

- Limits lifeline twisting
- Improves user experience

SUPER-TOUGH NYLON HOUSING

- Lightweight, compact and durable
- UV resistant

HEAT-SHRUNK CLEAR PVC COATING ON SHOCK PACK

- Easy to read label
- Easy to inspect
- Improved durability
- Visual impact indicator

SMALL OPENING SNAP HOOK OR BIG OPENING REBAR HOOK

- Zinc plated or Aluminium material

AVAILABLE MODELS

3.3 m and 6 m Web:

- High strength polyester thin webbing provides added durability and longevity

4.5 m Cable:

- With 5 mm galvanised cable

REBEL™ 3.3 METER WEB MODELS



REF : 3100424

Zinc plated snap hook with swivel:

- 19 mm opening
- 16 kN gate strength
- 1.5 kg - 3.3 m



REF : 3100443

Zinc plated snap hook:

- 17 mm opening
- 1 kN gate strength
- 1.2 kg - 3.3 m



MOST POPULAR MODEL

REF : 3100423

Zinc plated snap hook:

- 19 mm opening
- 16 kN gate strength
- 1.4 kg - 3.3 m

REF : 3100442

Aluminium rebar hook:

- 52 mm opening
- 16 kN gate strength
- 1.5 kg - 3.4 m



REBEL™ 6 METER WEB MODELS



MOST POPULAR MODEL

REF : 3100437

Zinc plated snap hook:

- 19 mm opening
- 16 kN gate strength
- 2.2 kg - 6 m



REF : 3100438

Zinc plated snap hook with swivel:

- 19 mm opening
- 16 kN gate strength
- 2.3 kg - 6 m



REF : 3100440

Zinc plated snap hook:

- 17 mm opening
- 1 kN gate strength
- 2 kg - 6 m



REF : 3100439

Aluminium rebar hook:

- 52 mm opening
- 16 kN gate strength
- 2.3 kg - 6.1 m



REF : 3100441

Zinc plated rebar hook:

- 60 mm opening
- 16 kN gate strength
- 2.5 kg - 6.1 m

REBEL™ 4.5 METER CABLE MODELS



MOST POPULAR MODEL

REF : 3590024

Zinc plated snap hook:

- 19 mm opening
- 16 kN gate strength
- 2.8 kg - 4.5 m

REF : 3590025

Zinc plated snap hook with swivel:

- 19 mm opening
- 16 kN Gate strength
- 2.9 kg - 4.5 m



REF : 3590027

Zinc plated snap hook:

- 17 mm opening
- 1 kN gate strength
- 2.6 kg - 4.5 m



REF : 3590026

Aluminium rebar hook:

- 52 mm opening
- 16 kN gate strength
- 2.9 kg - 4.6 m



REF : 3590028

Zinc plated rebar hook:

- 60 mm opening
- 16 kN gate strength
- 3.1 kg - 4.6 m





GLOBAL LEADER IN FALL PROTECTION

Capital Safety is the Global leader in fall protection equipment, systems and anchors.

Capital Safety est le leader mondial en matière d'équipement, de systèmes et d'ancrages de protections antichute.

Capital Safety ist weltweit führend auf dem Gebiet von Absturzsicherungs-ausrüstung, -systemen und Anschlagmöglichkeiten.

Capital Safety es el líder mundial en equipos, sistemas y anclajes de protección contra caídas.

Capital Safety is wereldleider in valbeveiligingsapparatuur, -systemen en verankeringen.

Capital Safety è leader globale nell'anticaduta per dispositivi di protezione individuale, sistemi e ancoraggi.

Capital Safety är globala inom utrustning, system och förankringar för fallskydd.

EUROPE, MIDDLE EAST & AFRICA

UK

5a Merse Road, North Moons Moat
Redditch, B98 9HL, UK
t: +44 (0) 1527 548 000
f: +44 (0) 1527 591 000

FRANCE

Le Broc Center, Bâtiment A
Z.1. 1re Avenue – BP15
06511 Carros Le Broc, Cedex, FRANCE
t: +33 (0) 4 97 10 00 10
f: +33 (0) 4 93 08 79 70

GERMANY

Hagener Straße 44
57489 Drolshagen, GERMANY
t: +49 (0) 2 76 18 33 82 29
f: +49 (0) 2 76 18 33 81 93

DUBAI

ME Branch Office, PO Box 17769
JAZFA, DUBAI – UAE
t: +971 (4) 88 11 4 66
f: +971 (4) 88 11 4 67

CUSTOMER SERVICES

 00 800 999 55500

 information@capitalsafety.com

 capitalsafety.com



All rights reserved. The material contained herein is copyrighted; no part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording or otherwise without prior written permission from Capital Safety.